



Glasroc F MULTIBOARD

the specialist board

Glasroc MultiBoard has changed for the better. Glasroc F MULTIBOARD is the new name reflecting the board's excellent fire protection properties. You'll also notice the boards are available in newly designed hoods and are fully CE marked.

Glasroc F MULTIBOARD is highly versatile and can be used for a wide variety of jobs, particularly in applications where fire, flexibility, strength or moisture resistance are important.



Excellent fire protection

Glasroc F MULTIBOARD is non-combustible, and depending on which thickness you choose, it can give up to 120 minutes fire resistance when building in fire-rated partitions.

Suitable for:

- Kitchens
- Boiler cupboard linings
- Garages
- Fire-rated partitions



Unmatched flexibility

Extra value can be added to many kinds of jobs by creating curved partitions. 6mm Glasroc F MULTIBOARD can curve to a radius of 600mm, creating stylish walls and ceilings.

Suitable for:

- Archways
- Curved walls and ceilings
- Hiding unwanted features (such as steel joists)
- Use in the **GypWall CURVE** and **Casoline CURVE** systems



Great strength

Glasroc F MULTIBOARD is a tough board, so it helps to resist cracking, shattering and denting in busy areas, keeping walls looking great for longer.

Suitable for:

- Hallways, corridors and stairwells
- Utility areas



Good finish

The smooth and durable white finish of the board means it can be left undecorated in utility areas. It can also be jointed or skim finished in rooms where looks are important.



Moisture resistance

The high moisture resistance in Glasroc F MULTIBOARD means it can be used both indoors and in semi-exposed areas.

Suitable for:

- Bathrooms
- Soffits
- Car port under-linings
- Ceramic tile backing

Available in 6mm, 10mm and 12.5mm thicknesses.

