Declaration of Performance



Glasroc® H TileBacker

ϵ

Unique identification code of the product type:	Glasroc H TileBacker	
Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Glasroc H TileBacker: 6mm, 12.5mm EN 15283 - GM-H1	
Intended use/s:	Non combustible, glass reinforced gypsum board for use in areas subject to high level moisture	
Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000	
Authorised representative:	N/A	
System/s of AVCP:	System 4 generally System 3 Reaction to Fire	
Harmonised standard:	EN 15283-1:2008 + A1:2009	
Notified body/ies:	MPA Hannover (NB 0764)	
Performed:	Reaction to Fire	
Under:	System 3	
European Assessment Document:	N/A	
European Technical Assessment:	N/A	
Technical Assessment Body:	N/A	
Notified body/ies:	N/A	
Declared performance/s:	The characteristics in the table below apply to all products	
	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): Intended use/s: Manufacturer: Authorised representative: System/s of AVCP: Harmonised standard: Notified body/ies: Performed: Under: European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:	

Essential characteristics	Performance	Harmonised technical specification
Longitudinal flexural strength (F)	258N (6mm) 538N (12.5mm)	EN 15283-1:2008 + A1:2009
Transverse flexural strength (F)	101N (6mm) 210N (12.5mm)	EN 15283-1:2008 + A1:2009
Shear strength (It)	NPD	EN 15283-1:2008 + A1:2009
Reaction to Fire (R2F)	A1	EN 15283-1:2008 + A1:2009
Water vapour permeability (μ)	10	EN 15283-1:2008 + A1:2009
Impact resistance¹ (→I)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Direct airborne sound insulation ¹ (R)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Acoustic absorption 1 (α)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Thermal resistance (as conductivity) (λ)	0.3W/mK	EN 15283-1:2008 + A1:2009

mentioned in 2 above.

¹ These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

Declaration of Performance



Glasroc® H TileBacker

 ϵ

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

East Leake 09/12/2020

Matt Pullen, Managing Director, British Gypsum Place and date of issue