## **Declaration of Performance**



#### Glasroc® X Sealant

# $\epsilon$

1	Unique identification code of the product type:	Glasroc X Sealant
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Glasroc X Sealant
3	Intended use/s:	Sealant for non-structural use in joints in buildings
4	Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5	Authorised representative:	N/A
6	System/s of AVCP:	System 3
7	Harmonised standard: Notified body/ies:	BS EN 15651-1:2012 GINGER CEBTP, Notified Body No. 0074
8	European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:	N/A N/A N/A
9	Declared performance/s:	The characteristics in the table below apply to all products mentioned in 1 above.  Substrate: Anodised Aluminium Tested Class: 25 LM CC Scope: Facade EXT/INT

Essential characteristics	Test standards	Performance	Harmonised technical specification		
Reaction to Fire	BS EN 13501-1:2007 + A1: 2009	Class E	BS EN 15651-1:2012		
Release of dangerous substances	-	None	BS EN 15651-1:2012		
Water tightness and air-tightness detern	ter tightness and air-tightness determined by:				
Loss of volume (%)	EN ISO 10563	≤ 10	BS EN 15651-1:2012		
Resistance to flow (mm)	EN ISO 7390	≤ 3	BS EN 15651-1:2012		
Adhesion/cohesion properties at maintained extension after water immersion (23°C)	EN ISO 10590	NF	BS EN 15651-1:2012		
Adhesion/cohesion properties (-30°C)	EN ISO 8339 modified	≤ 0.9MPa	BS EN 15651-1:2012		
Adhesion/cohesion properties at maintained extension (-30°C)	EN ISO 8340 modified	NF <sup>1</sup>	BS EN 15651-1:2012		
Durability	EN ISO 8340 EN ISO 9047 EN ISO 10590	Pass	BS EN 15651-1:2012		

 $<sup>^{\</sup>rm 1}$  NF - No failure according to EN ISO 11600

### **Declaration of Performance**



Glasroc® X Sealant

 $\epsilon$ 

#### 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

East Leake 02/01/2019

Matt Pullen, Managing Director, British Gypsum Place and date of issue