Product data sheet

Glasroc® X Sealant



Glasroc X Sealant is a silicone-based sealant and adhesive.

Where to use

Use it for the perimeter sealing of Glasroc X Sheathing Boards to maintain optimum performance.



Product information

Composition

This product is a silicone-based sealant.

Colour

White.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

BS EN 15651-1:2012.

Declarations of Performance (DoP) available Click here.

Reaction to fire	Е
Mould resistance	Yes

Product data sheet

Glasroc® X Sealant



Installation guidance

Limitations of use

Do not use on surfaces that bleed oils or plasticisers or in contact with bitumen or asphalt. Do not attempt to sand down this product.

Application

Sealing applications

All surfaces must be clean, dry and free from dust, grease and any loose materials.

Carefully cut one end off the foil and fit it into the caulking gun.

Cut the nozzle at an angle to provide a suitable diameter bead for the joint to be sealed, normally 6mm.

Apply sealant into the joint ensuring good contact is made with the sides of the joint, and ensuring continuity of the seal where required.

Tooling can be carried out within 10 minutes if necessary, using a wet tooling stick, trowel or spatula.

Surplus sealant can be removed if necessary within 10 minutes using a damp cloth or sponge.

Product data sheet

Glasroc® X Sealant



Sitework

Packaging overview

600ml foil sausage, supplied in cartons of 12 foils.

Quantitiy per carton	12 foils
Quantity per pallet	75 cartons

Storage

Store in a dry place between 5°C and 25°C; keep out of sunlight and protect from frost.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

Shelf life

2 years in original unopened packaging when stored correctly.

Safety Data Sheet

Safety Data Sheet (SDS) available. Click here.

Environmental


Recyclability

This product cannot be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements.





"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.