Repair range selector guide



	Trade Professional		Pro Plasterer
	EasiFill 60 The state of the st	Enifell 20	Bonding 60
ıct	Gyproc EasiFill 60	Gyproc EasiFill 20	Thistle Bonding 60

Product	Gyproc EasiFill 60	Gyproc EasiFill 20	Thistle Bonding 60
Product description	Easy to finish, quick to decorate	Easy, fast finish for small areas	Deep patches fast
What's it best for?	Up to 6mm deep holes, patches and cracks	Up to 6mm deep holes, patches and cracks	Small patches, repairs or chases deeper than 5mm
What sort of jobs can it do?	Filling around socket boxes, repairing movement cracks, filling knocks or damage. Patching larger areas of plasterboard	Filling around socket boxes, repairing movement cracks, filling knocks or damage. Patching small areas of plasterboard	Smaller repairs on water or impact damaged plaster, filling pipe or cable chases, deep holes (built up in coats)
low do I finish it?	Sand to a fine, white finish before painting	Sand to a fine, white finish before painting	Finish with a Thistle or ThistlePro plaster, following application instructions as required
low long does it stay workable?	60 mins	20 mins	45 mins
low quickly can I finish it?*	130 mins	60 mins	75 min
low soon can I decorate it?*	24 hours	24 hours	-
Pack size	10kg bag	5kg bag	10kg tub, 12.5kg or 25kg bags
Where to use - background surface			
ightweight blocks, common bricks	-	-	-
Indercoat plaster	-	-	-
Pense blocks	-	-	Υ
Plasterboards and Glasroc boards	Y	Υ	Υ
Concrete	-	-	Υ
ainted surfaces	-	-	Υ
Metal lathing	-	-	Y

Thistle Bond-it may be required for repairs on smooth/low suction such as dense blocks, MR boards, concretes and painted surfaces. Thistle GypPrime may be required for very high suction backgrounds such as undercoat plaster.



^{*} Dependent on environmental conditions.