



Application area: Gyproc® Firestopping

Number of Years: 25 years²

The **SpecSure®** Warranty covers British Gypsum Gyproc® Firestopping within new build British Gypsum and Isover partition Systems¹, performing as specified with a working life of 25 years². By choosing a British Gypsum and Isover System developed, tested and supported by drywall and insulation specialists, you're protecting the future of the building and its users.

25 years²
SpecSure® Systems
Warranty for Gyproc®
Firestopping

Systems Covered by this Warranty:

Gyproc® Firestopping in new build British Gypsum and Isover partition Systems

What is not covered:

- Gyproc® Firestopping in existing partition structures including existing British Gypsum systems.
- Gyproc® Firestopping in other branded partition Systems.
- Gyproc® Firestopping in rigid walls and floors (e.g. concrete, aerated concrete, or masonry, as defined in the UKTAs for the relevant Gyproc® Firestopping products)
- Gyproc® Firestopping in timber floors (as defined in the UKTAs for the relevant Gyproc® Firestopping products)

The British Gypsum and Isover Promise

SpecSure® is our promise that the British Gypsum and Isover System you have chosen:

Comprises only components manufactured or specified by British Gypsum and Isover that are designed to work together to deliver the specified level of performance;

- Has been developed utilising the technical expertise and experience of British Gypsum and Isover drylining and insulation specialists;
- References claimed performances that have been tested in UKAS accredited fire, acoustic and structural test laboratories. We regularly retest our products to ensure consistency of performance when incorporated within our Systems;
- Will be supported, on and off-site, as required at every stage of the project by our team of drylining and insulation technical experts;
- Will achieve every performance as claimed and will continue to do so throughout the warranty period of the working life of 25 years²;
- Will be repaired or replaced by British Gypsum and Isover in the unlikely event of system performance failure attributed to a defective product. **Please refer to our Terms and Conditions.**

¹ Systems comprised of genuine components specified by British Gypsum and Isover, and installed as stipulated within our installation instructions provided in The White Book, on british-gypsum.com, isover.co.uk or in written guidance provided by our technical support team. Where we have a solution tested, we offer a **SpecSure®** warranty including non-loadbearing timber systems which can be found [here](#).

² The provisions made in the United Kingdom Technical Assessment for Gyproc Firestopping are based on an assumed working life of the (product) of 25 years, provided that the conditions laid down in the manufacturers datasheet and instructions for the packaging/transport/storage/installation/use/repair are met.

Gyproc® Firestopping

To Qualify for SpecSure® when using Gyproc Firestopping

Specify, install and finish Gyproc® Firestopping within new build British Gypsum and Isover Systems in line with our recommendations provided in the current British Gypsum White Book, on british-gypsum.com, isover.co.uk or written guidance provided by our technical support team, including Project Specification Managers, Technical Support and Onsite Consultants.

The Systems must comprise only genuine components specified by British Gypsum and Isover. We cannot guarantee that the use of other components will meet our rigorous performance and quality standards when installed in our tested Systems.

Conditions

In order to qualify for **SpecSure®** warranty when using Gyproc® Firestopping the following conditions must be met.

Design stage

Gyproc® Firestopping must be specified in line with the systems on the British Gypsum website or as advised in writing by the technical support team.

Installation

We recommend the use of competent third party accredited installers to install Gyproc Firestopping systems. All genuine components must be used as per the specified system. If any part of the System including accessories, insulation and finish is substituted, it will not qualify for **SpecSure®** warranty. Gyproc® Firestopping must be installed in line with the detailed design and installation guidelines that can be accessed on british-gypsum.com or from our technical support team.

Inspections

It is the responsibility of the warranty holder to ensure inspections are conducted at least annually or more frequently after building modifications or incidents that could affect the integrity of the firestopping. Records must be kept and completed in order to qualify for **SpecSure®** warranty of the working life of 25 years².

How to claim

In the unlikely event something goes wrong British Gypsum and Isover are here to support. **Please see full Terms and Conditions.**

² The provisions made in the United Kingdom Technical Assessment for Gyproc Firestopping are based on an assumed working life of the (product) of 25 years, provided that the conditions laid down in the manufacturers datasheet and instructions for the packaging/transport/storage/installation/use/repair are met.