Declaration of Performance



Gyproc® DriWall Adhesive

$C \in$

1	Unique identification code of the product type:		Gyproc DriWall Ad	Gyproc DriWall Adhesive	
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):		Gyproc DriWall Ac	Gyproc DriWall Adhesive	
3	Intended use/s:			Gypsum based adhesive for use in drywall systems, on high, medium or low suction backgrounds	
4	Manufacturer:		East Leake, Lough	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000	
5	Authorised representative:		N/A	N/A	
6	System/s of AVCP:			System 4 generally System 3 Reaction to Fire	
7	Harmonised standard: Notified body/ies: Performed: Under:		EN 14496:2005 Applus+ (NB 0370 Reaction to Fire System 3	Applus+ (NB 0370) Reaction to Fire	
8	European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:		N/A N/A N/A N/A	N/A N/A	
9	Declared performance/s:			The characteristics in the table below apply to all products mentioned in 2 above.	
E	Essential characteristics	Performance		Harmonised technical specification	
F	Reaction to Fire (R2F) A1			EN 14496:2005	
Е	Bond strength	>0.06MPa		EN 14496:2005	

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dangerous Substances (DS)

Dean O'Sullivan, Managing Director, British Gypsum

East Leake 23/03/23

EN 14496:2005

Place and date of issue