

Declaration of Performance

CasoLine® Quick-Lock Grid hangers



1 Unique identification code of the product type:	CasoLine Quick-Lock
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	CasoLine Quick-Lock Grid Hangers
3 Intended use/s:	Suspension system components for ceilings in building interiors
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	Loadbearing capacity: System 3 Reaction to Fire: System 3 or 4 Durability: System: 4
7 Harmonised standard: Notified body/ies:	EN 13964:2014 Loadbearing capacity tests carried out by NB0432 MPA Dortmund and NB1153 TNO Delft Reaction to Fire: Galvanized steel Commission decision 96/603/EC; Coilcoated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251 Durability: EN 13964 Table 8
8 European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:	N/A N/A N/A N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Normal service load (N)	255	EN 13964:2014
Reaction to Fire (R2F)	Class A1	EN 13964:2014
Durability	Class B	EN 13964:2014

Declaration of Performance

CasoLine® Quick-Lock Grid hangers



10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....

Matt Pullen, Managing Director, British Gypsum

East Leake 09/12/2020

.....

Place and date of issue