

Declaration of Performance

Gyproc® Acrylic Fire Sealant

British Gypsum
SAINT-GOBAIN

**UK
CA**

1 Unique identification code of the product type:	Gyproc Acrylic Fire Sealant
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Gyproc Acrylic Fire Sealant 300 ml Foil, Gyproc Acrylic Fire Sealant 310 ml Cartridge, Gyproc Acrylic Fire Sealant 600 ml Foil
3 Intended use/s:	Linear Joint & Gap Seal and Penetration Seal
4 Manufacturer:	Saint-Gobain Construction Products UK Ltd t/a British Gypsum Saint-Gobain House East Leake, Loughborough Leicestershire LE12 6JU Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	AVCP-System 1
7 Designated standard: Approved body/ies:	N/A N/A
8 UK Assessment Document: UK Technical Assessment: Technical Assessment Body: Approved body/ies:	EAD 350454-00-1104 (September 2017) EAD 350141-00-1106 (September 2017) 0843-UKTA-25/0019 (issued 28/11/2025) 0843-UKTA-25/0020 (issued 28/11/2025) UL International (UK) Ltd 0843
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	B -s1 - d0	EN 13501-1:2018
Resistance to Fire	Penetration seals - 0843-UKTA-25-0019, Annex A Linear gap seals - 0843-UKTA-25-0020, Annex A	Penetration seals - EN 13501-2, EN 1366-3 Linear gap seals - EN 13501-2, EN 1366-4
Air permeability	Penetration seals - 0843-UKTA-25-0019, Annex B Linear gap seals - 0843-UKTA-25-0020, Annex B	EN 1026
Water permeability	NPD	Penetration seals - EAD 350454-00-1104, Annex C Linear gap seals - EAD 350141-00-1106, Annex C & EN 12390-8
Release of dangerous substances	As the manufacturer we declare that there is no release of dangerous substances during the installation or use of this product. See safety data sheets.	
Mechanical resistance and stability	NPD	EOTA TR 001:2003
Resistance to impact/movement	NPD	EOTA TR 001:2003

Table continues overleaf

Declaration of Performance

Gyproc® Acrylic Fire Sealant



Airborne sound insulation	NPD	EN 10140-1,2,4,5 / EN ISO 717-1
Thermal properties	NPD	EN 12664, EN 12667, EN 12939, EN ISO 8990, EN ISO 6946, EN ISO 14683, EN ISO 10211, EN ISO 10456
Water vapour permeability	NPD	EN ISO 12572, EN 12086, EN ISO 10456
Durability and serviceability	Z ₂	Penetration seals – EAD 350454-00-1104, Clause 2.2.9 Linear gap seals – EAD 350141-00-1106, Clause 2.2.12
Adhesion	NPD	Penetration seals – EOTA TR 001:2003 Linear gap seals – EOTA TR 001:2003, ISO 11600 & EAD 350141-00-1106, Clause 2.2.13

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....

Mike Emson, Chief Operating Officer, British Gypsum

East Leake 28/11/2025

.....

Place and date of issue