

Declaration of Performance

Gyproc® Fire Mortar

 **British Gypsum**
SAINT-GOBAIN

**UK
CA**

1 Unique identification code of the product type:	Gyproc Fire Mortar
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Gyproc Fire Mortar 15 kg
3 Intended use/s:	Reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetrations of multiple services
4 Manufacturer:	Saint-Gobain Construction Products UK Ltd t/a British Gypsum Saint-Gobain House East Leake, Loughborough Leicestershire LE12 6JU Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	AVCP-System 1
7 Designated standard: Approved body/ies:	N/A
8 UK Assessment Document: UK Technical Assessment: Technical Assessment Body: Approved body/ies:	EAD 350454-00-1104 (September 2017) UKTA-25/0027 (issued 28/11/2025) UL International (UK) Ltd 0843
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	Class A1	EN 13501-1: 2018
Resistance to Fire	0843-UKTA-25/0027, Annex A	EN 13501-2, EN 1366-3
Air permeability (material property)	0843-UKTA-25/0027, Annex B	EN 1026
Water permeability (material property)	NPD	EAD 350454-00-1104, Annex C
Release of dangerous substances	Use categories: IA1, S/W2 As the manufacturer we declare that Gyproc Fire Mortar is compliant with the requirements of current EU legislation on material safety. See safety data sheets.	
Mechanical resistance and stability	Suitable for use in walls and floors in Zone Types I, II, III & IV*	EOTA TR 001:2003
Adhesion		EOTA TR 001:2003
Resistance to impact/movement		EOTA TR 001:2003
Airborne sound insulation	NPD	EN 10140-1,2,4,5 / EN ISO 717-1

* At dimensions up to those given in 3.3 and with soft and hard body impact – Refer to 0843 - UKTA-25/0027

Table continues overleaf

Declaration of Performance

Gyproc® Fire Mortar

British Gypsum
SAINT-GOBAIN

**UK
CA**

Thermal properties	NPD	EN 12664, EN 12667, EN 12939, EN ISO 8990, EN ISO 6946, EN ISO 14683, EN ISO 10211, EN ISO 10456
Water vapour permeability	NPD	EN ISO 12572, EN 12086, EN ISO 10456
Durability and serviceability	Z ₂	EAD 350454-00-1104, Clause 2.2.9

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Mike Emson, Chief Operating Officer, British Gypsum

East Leake 28/11/2025

.....
Place and date of issue