

Declaration of Performance

Gyproc® QuickSand



1 Unique identification code of the product type:	Gyproc QuickSand
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Gyproc QuickSand EN 13963 3A
3 Intended use/s:	Filling and finishing joints in plasterboard systems
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	System 4 generally System 3 Reaction to Fire
7 Harmonised standard:	EN 13963:2005
Notified body/ies:	MPA Hannover (NB 0764)
Performed:	Reaction to Fire
Under:	System 3
8 European Assessment Document:	N/A
European Technical Assessment:	N/A
Technical Assessment Body:	N/A
Notified body/ies:	N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A2-s1, d0	EN 13963:2005
Flexural strength (F)	NPD	EN 13963:2005

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....

Matt Pullen, Managing Director, British Gypsum

East Leake 17/12/2020

.....

Place and date of issue