

# Declaration of Performance

Thistle® DriCoat



<b>1 Unique identification code of the product type:</b>	Thistle DriCoat
<b>2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</b>	Thistle DriCoat
<b>3 Intended use/s:</b>	Renovating plastering mortar for internal wall linings (base coat)
<b>4 Manufacturer:</b>	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0)115 945 1000
<b>5 Authorised representative:</b>	N/A
<b>6 System/s of AVCP:</b>	System 4 generally
<b>7 Designated standard: Approved body/ies:</b>	EN 998-1:2016 N/A
<b>8 European Assessment Document: European Technical Assessment: Technical Assessment Body: Approved body/ies:</b>	N/A N/A N/A N/A
<b>9 Declared performance/s:</b>	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A1	EN 998-1:2016
Adhesive strength	0.8N/mm <sup>2</sup> , FP A	EN 998-1:2016
Compressive strength	CS II	EN 998-1:2016
Dry Bulk Density (declared)	725kg/m <sup>3</sup>	EN 998-1:2016
Water absorption	6.52kg/m <sup>2</sup> after 24 hr	EN 998-1:2016
Water vapour Diffusion Coefficient (μ)	12.22	EN 998-1:2016
Thermal conductivity (λ)	0.17W/m.K	EN 998-1:2016

# Declaration of Performance

Thistle® DriCoat

 **British Gypsum**  
SAINT-GOBAIN

**UK  
CA**

---

## 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



East Leake 17/12/2021

.....  
**Dean O'Sullivan, Managing Director, British Gypsum**

.....  
**Place and date of issue**