Declaration of Performance



Thistle® Bonding 60

UK

1	Unique identification code of the product type:	Thistle undercoat plaster range	
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Thistle Bonding 60 Type B4/20/2 and C3/20	
3	Intended use/s:	Gypsum plaster for internal wall linings (base coat)	
4	Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0)115 945 1000	
5	Authorised representative:	N/A	
6	System/s of AVCP:	System 4 generally System 3 Reaction to Fire	
7	Designated standard: Approved body/ies:	EN 13279-1:2008 BRE Global Ltd (AB 0832)	
	Performed: Under:	Reaction to Fire System 3	
8	European Assessment Document:	N/A	
	European Technical Assessment:	N/A	
	Technical Assessment Body:	N/A	
	Approved body/ies:	N/A	
9	Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.	

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A1	EN 13279-1:2008
Thermal conductivity	0.30W/mK (Bonding 60)	EN 13279-1:2008
Thermal resistance (TR)	0.037m ² K/W	EN 13279-1:2008
Direct airborne sound resistance	Refer to product literature	EN 13279-1:2008

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Oser of Die

East Leake 01/06/2022

Dean O'Sullivan, Managing Director, British Gypsum

Place and date of issue