

# Declaration of Performance

Gyproc® Sealant

**British Gypsum**  
SAINT-GOBAIN



<b>1 Unique identification code of the product type:</b>	Gyproc Sealant
<b>2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</b>	Gyproc Sealant
<b>3 Intended use/s:</b>	F-INT acrylic sealant and adhesive used for sealing small air gaps
<b>4 Manufacturer:</b>	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
<b>5 Authorised representative:</b>	N/A
<b>6 System/s of AVCP:</b>	System 4 generally
<b>7 Harmonised standard: Notified body/ies:</b>	BS EN 15651-1:2012 N/A
<b>8 European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:</b>	N/A N/A N/A N/A

**9 Declared performance/s:** The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	F	BS EN 15651-1:2012
Water tightness and air-tightness determined by:		
Resistance to flow (mm)	≤5	BS EN 15651-1:2012
Loss of volume (%)	≤45	BS EN 15651-1:2012
Tensile properties: Elongation at break at 23°C (%)	≥25	BS EN 15651-1:2012
Durability	Pass	BS EN 15651-1:2012

## 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....  
**Matt Pullen, Managing Director, British Gypsum**

East Leake 01/04/2017

.....  
**Place and date of issue**