

Declaration of Performance

Gyproc® Sealant

British Gypsum
SAINT-GOBAIN

**UK
CA**

1 Unique identification code of the product type:	Gyproc Sealant
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Gyproc Sealant
3 Intended use/s:	F-INT acrylic sealant and adhesive used for sealing small air gaps
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	System 4 generally
7 Harmonised standard: Notified body/ies:	BS EN 15651-1:2012 N/A
8 European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:	N/A N/A N/A N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	F	BS EN 15651-1:2012
Water tightness and air-tightness determined by:		
Resistance to flow (mm)	≤5	BS EN 15651-1:2012
Loss of volume (%)	≤45	BS EN 15651-1:2012
Tensile properties: Elongation at break at 23°C (%)	≥25	BS EN 15651-1:2012
Durability	Pass	BS EN 15651-1:2012

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dean O'Sullivan, Managing Director, British Gypsum

East Leake 8/12/2021

Place and date of issue