# **Product data sheet**

Gypframe® SIF2 Floor Channel



A steel channel with an integral neoprene acoustic isolator to reduce impact sound transmission.

### Where to use

SIF floor channels are located directly on top of the joists ready to receive cut pieces of square edge Gyproc Plank. Gypframe SIF2 can be used for joists more than 75mm wide.

# Certifications

Environmental Product Declaration (EPD) available Click here.



# **Product information**

#### Composition

Cold-roll steel formed using the patented UltraSTEEL<sup>\*</sup> process. With an integral neoprene acoustic isolator

Col	our
Ste	el

Where to buy Click here.

DIMENSIONS AND WEIGHTS		
Lengths available (mm)	2000	
Bespoke length available	Yes	56mm
Width (mm)	84	
Gauge (mm)	0.60	−− 84mm   E
Weight (kg/lm)	0.46	

# Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

#### Standards

EN 14195:2005.

Declarations of Performance (DoP) available Click here.

Reaction to fire	No performance determined, please contact Technical Support on british-gypsum.com for product component risk assessment
Yield strength (N/mm²)	210

# Installation guidance

Please see our White Book online for more information about installing and handling British Gypsum systems and Gypframe profiles. See the Gypframe Safety Data Sheet for guidance on health and safety, handling and storage.

# **Fixing compatibility**

Check the system specification for the required British Gypsum screw type.

© British Gypsum, 2023.

# **Product data sheet**



Gypframe® SIF2 Floor Channel

## Sitework

### Storage

Store inside where possible, for outdoor storage please ensure that the products are securely covered with an anchored polythene sheet or tarpaulin to protect from dampness and rain.

#### Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

When handling British Gypsum Gypframe metal please ensure you are wearing puncture-resistant protective gloves, sleeves and appropriate safety footwear.

Personal protective equipment for eye and face protection should also be worn that comply with European Standard EN166.

#### Safety Data Sheet

Safety Data Sheet (SDS) available. Click here.

#### **Packaging overview**

These components are supplied in packs banded together with nylon strapping.

Quantity per pack

10



British Gypsum Head Office, East Leake, Loughborough, Leicestershire, LE12 6HX T: 0115 945 1000 british-gypsum.com

#### bsi, ISO 9001 Quality Management FM550533 OHS550586 EMS543324 ENMS606206

"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.

# Environmental

#### Recyclability

Gypframe components are 100% recyclable.

#### Disposal

Waste from Gypframe metal framing components is fully recyclable. The European Waste Catalogue code i s 12 01 01.

#### **BES 6001 classification**

Excellent.