

Product data sheet

Gyproc® Corner Tape

Gyproc Corner Tape is a paper joint tape bonded to two steel strips.

Where to use

Use it to reinforce external angle joints in plasterboard constructions.



Product information

Composition

This product is made from paper with metal strips.

Colour

White.

Lengths available (m)

30.

Width (mm)

50 approx.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

EN 14353:2007+A1:2010.

Declarations of Performance (DoP) available [Click here](#).

| | |
|------------------|---|
| Reaction to fire | E |
|------------------|---|

Installation guidance

Cutting

Cut to length with snips, allowing for some thermal movement, e.g. a piece for a 2.4m floor to ceiling joint should be cut with 3mm clearance in length.

Fixing

Check boarding for secure fixing and damage and correct if necessary.

Cut to length, mitring corners around window openings etc.

Apply a coat of Gyproc Joint Filler or Gyproc EasiFill to both sides of the joint.

Pre-fold the Gyproc Corner Tape to the correct angle and carefully press into the jointing compound, ensuring there is no trapped air and that the alignment is correct. Remove excess joint compound and allow to set.

Finish the joint by applying further coat(s) as required, feathered out onto the face of the boards, using any suitable Gyproc joint compound (not Gyproc Joint Filler for the final coat).

When fully dry, sand to a final finish taking care not to damage the paper, and decorate.

Product data sheet

Gyproc® Corner Tape



Sitework

Packaging overview

30m roll in cardboard dispensing carton, 5 boxes per carton.

| | |
|---------------------|----------|
| Quantity per carton | 5 rolls |
| Quantity per pallet | 80 boxes |

Storage

Store in a dry place and keep out of sunlight.

Environmental

Recyclability

This product can be recycled with paper in accordance with local authority requirements.

Disposal

Segregate the product from non-gypsum waste for recycling where possible, and dispose of it according to local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.