Product data sheet

Gyproc® Drywall Metal Edge Bead 12.5mm

Gyproc Drywall Metal Edge Bead 12.5mm is a galvanised steel angle bead with expanded wings.

Where to use

Use it to form a defined edge to plasterboard areas.

Product information

Composition
This product is made from galvanised steel.

Colour
Steel.

Lengths available (mm)
2400, 3000.

Width (mm)
12.5.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards
EN 14353:2007+A1:2010.
Declarations of Performance (DoP) available Click here.

Reaction to fire	A1

Installation guidance

Cutting
Measure and cut bead with appropriate tin snips.

Fixing
To be installed using suitable fixings by others.

© British Gypsum, 2023.

Sitework

Storage

Store inside where possible, for outdoor storage please ensure that the products are securely covered with an anchored polythene sheet or tarpaulin to protect from dampness and rain.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

When handling British Gypsum metal beads please ensure you are wearing puncture-resistant protective gloves, sleeves and appropriate safety footwear.

Personal protective equipment for eye and face protection should also be worn that comply with European Standard EN166.

Packaging overview

Supplied in a cardboard box.

Quantity per carton	20 beads

Environmental

Recyclability

Metal beads are 100% recyclable.

Disposal

Segregate the product from non-gypsum waste for recycling where possible, and dispose of it according to local authority requirements.

SAINT-GOBAIN

British Gypsum

Head Office, East Leake,
Loughborough,
Leicestershire, LE12 6HX
T: 0115 945 1000

british-gypsum.com

bsi. ISO 9001 Quality Management FM550533 | ISO 45001 Occupational Health and Safety Management OHS550586 | ISO 14001 Environmental Management EMS543324 | ISO 50001 Energy Management ENMS606206

"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.