

Product Data Sheet

Gyproc® Drywall Primer

Gyproc Drywall Primer is a primer for new plasterboard surfaces to prepare them for painting.

Where to use

Use it after joint treatment is complete to protect plasterboard surfaces from UV degradation and to equalise suction and texture for painting.



Product information

Composition

This product is made up of a polymer dispersion based primer.

Nominal volume (litres)

10

Colour

Magnolia.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Maximum VOC content (g/l)	<10
---------------------------	-----

Limitations of use

Gyproc Drywall Primer may be used as a base for most wallcoverings, but solvent-based wall covering adhesives should not be used.

Effect of temperature

Ambient and background temperature must be maintained above 5°C until fully dry. The product should be stored between 5°C and 30°C.

Application

Background preparation: plasterboards

Board and joint treatment surfaces should be dry, clean and dust-free before application.

Can be applied by brush or medium-pile roller.

Mixing up

Stir before use, do not dilute.

Coverage per litre (m²)	15 (one coat)
-------------------------	---------------

Painting and wallpapering

Painting

Allow the primer to fully dry before painting.

Product Data Sheet

Gyproc® Drywall Primer



Sitework

Storage

Store and use in temperature range of 5-30°C. Avoid stacking more than four tubs high to prevent damage to the packaging.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

Safety Data Sheet

Safety Data Sheet (SDS) available [Click here](#).

Shelf life

This product has a shelf life of 12 months and is marked with a use-by-date.

Packaging overview

10 litre plastic tub, supplied palletised.

Quantity per pallet	48 tubs
---------------------	---------

Environmental

Recyclability

This product cannot be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements. Do not empty into drains or watercourses.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.