

Product Data Sheet

Gyproc® EasiFill 60

Gyproc EasiFill 60 is a combined setting and air-drying, gypsum based material.

Where to use

Use it to bulk-fill and finish holes and damage and as a plasterboard joint filler and finish.

Certifications

Environmental Product Declaration (EPD) available [Click here](#).



Product information

Composition

This is a gypsum and limestone based filler with additives to control rheology and water retention.

Colour

Off-white.

Nominal weight (kg)

5kg and 10kg bags.

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

EN 13963:2005, Type 3B.

Declarations of Performance (DoP) available [Click here](#).

Effect of moisture and condensation

Don't expose the product to moisture repeatedly or for long periods of time, as this can cause it to lose strength and adhesion.

Effect of temperature

Ambient and background temperature must be maintained above 5°C until fully dry.

Reaction to fire	A1
------------------	----

Product Data Sheet

Gyproc® EasiFill 60

Application

Background preparation: plasterboards

Backgrounds should be reasonably dry, clean and dust-free.

Mixing up

The powder should be added gradually to clean water in a clean mixing vessel, stirring continuously until a smooth creamy consistency is achieved. Excessive mechanical mixing should be avoided, and only low-speed mixers used. Once the material starts to set it must be used quickly or discarded, it cannot be remixed.

Applying to different substrates

Apply Gyproc EasiFill 60 to the joint to embed the joint tape and immediately overcoat to fully fill the tapered board edges and just feather out onto the board surface. Allow to set for a minimum of 130 minutes before applying the next coat.

Painting and wallpapering

Painting

Apply Gyproc Drywall Primer as soon as practicable after sanding, in preparation for painting.

Wallpapering

Apply Gyproc Drywall Sealer as soon as practicable after sanding, in preparation for applying wallcoverings.

Tiling

Not suitable as a background for direct application of tiles.

Snagging and minor repairs

Gyproc EasiFill can be used for repairing small holes, cracks or damages, patching small areas of plaster or plasterboard.

Working time: maximum	60 minutes
Set time: minimum	75 minutes
Minimum recommended time before recoating	130 minutes
Water requirements per bag (litres)	3.25 L for 5kg bags, 6.5 L for 10kg bags

Product Data Sheet

Gyproc® EasiFill 60

Sitework

Storage

Bags should be stored inside on a flat and stable surface, away from any sources of moisture, heat or direct sunlight. If storing on a concrete floor, use dry timber platforms. The bags should not be stored near any edges, openings, walkways or traffic areas, where they could fall or cause obstruction. Damaged or opened bags should be used first or discarded appropriately.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

Safety Data Sheet

Safety Data Sheet (SDS) available [Click here](#).

Shelf life

Stored correctly, this product has a shelf life of six months, and bags are marked with a use by date so you can use them in strict rotation.

Packaging overview

Quantity per pallet	200 bags (5kg) 80 bags (10kg)
Pallet: nominal height (mm)	1060
Pallet: nominal length (mm)	1200
Pallet: nominal depth (mm)	1000
Pallet: nominal weight (tonnes)	0.8

Environmental

Recyclability

This product can be recycled.

Disposal

Segregate the product from non-gypsum waste for recycling where possible, and dispose of it according to local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.