

# Product data sheet

## Gyproc® FireStrip

Gyproc FireStrip is a soft extruded intumescent gap sealer.

### Where to use

Use it to maintain fire resistance located between the soffit and the partition when forming a deflection head.



### Product information

#### Composition

This product is a self-adhesive butyl extruded intumescent gap sealer.

#### Colour

Grey.

#### DIMENSIONS AND WEIGHTS

Lengths available (mm)	3600
Width (mm)	25
Nominal thickness (mm)	3
Length tolerance: maximum (mm)	+300
Length tolerance: minimum (mm)	0

### Installation guidance

#### Cutting

Single lengths can be made by running a sharp blade between the strips while it is still on the reel.

#### Application

##### Preparation

All surfaces must be sound, clean, dry and free from oil, grease, dust and other loose material.

##### Application

Unreel the Gyproc FireStrip and place the exposed side on to the required surface. Press down firmly along the length to achieve good contact with the surface.

Once the strip is secured in place it can be cut to length using a sharp knife.

When ready to apply to the structural soffit, remove the backing liner and install into position.

# Product data sheet

## Gyproc® FireStrip



### Sitework

#### Packaging overview

Supplied in a cardboard box.

Quantity per pack	5 lengths
-------------------	-----------

#### Storage

Store in a dry place between 5 °C and 25 °C; keep out of sunlight and protect from frost.

#### Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

#### Shelf life

24 months.

#### Safety Data Sheet

Safety Data Sheet (SDS) available [Click here](#).

### Environmental

#### Recyclability

This product cannot be recycled. The external cardboard packaging can be recycled.

#### Disposal

Waste should be disposed of in accordance with local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: [british-gypsum.com](http://british-gypsum.com). For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.