

# Product data sheet

## Gyproc® LevelLine



Gyproc LevelLine is a high strength 70mm wide corner tape.

### Where to use

Use it for internal and external angles in jointed systems.

---

### Product information

#### Colour

White.

#### Lengths available (mm)

3000.

#### Width (mm)

70.

#### Where to buy

[Click here.](#)

---

### Installation guidance

#### Limitations of use

This product should not be finishing by skimming.

#### Cutting

Cut to length with snips or scissors, allowing for some thermal movement, e.g. a piece for a 2.4m floor to ceiling joint should be cut with 3mm clearance in length.

#### Fixing

Check boarding for secure fixing and damage and correct if necessary.

Cut to length, mitring corners around window openings etc.

Apply a coat of Gyproc Joint Filler or Gyproc EasiFill to both sides of the joint.

Pre-fold the Gyproc LevelLine to the correct angle and carefully press into the jointing compound, ensuring there is no trapped air and that the alignment is correct. Remove excess joint compound and allow to set.

Finish the joint by applying further coat(s) as required, feathered out onto the face of the boards, using any suitable Gyproc joint compound (not Gyproc Joint Filler for the final coat).

When fully dry, sand to a final finish taking care not to damage the paper, and decorate. This product should not be finished by skimming.

# Product data sheet

## Gyproc® LevelLine



### Sitework

#### Packaging overview

30m roll in cardboard carton, 12 rolls per carton.

Quantity per carton	12 rolls
Quantity per pallet	24 cartons

### Storage

Store in a dry place between 5°C and 25°C, keep out of sunlight and protect from frost.

### Environmental

#### Recyclability

This product cannot be recycled.

#### Disposal

Waste should be disposed of in accordance with local authority requirements.

**SAINT-GOBAIN**

**British Gypsum**  
Head Office, East Leake,  
Loughborough,  
Leicestershire, LE12 6HX  
T: 0115 945 1000



"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: [british-gypsum.com](http://british-gypsum.com). For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.