

Product Data Sheet

Thistle® GypPrime

Thistle GypPrime is a suction control primer to give a lower suction base on very dry backgrounds.

Where to use

Use it to pre-treat surfaces where suction is extremely high. When using ThistlePro DuraFinish over undercoat plasters the surface should be prepared using Thistle GypPrime.



Product information

Composition

This product is made up of a polymer dispersion based primer.

Colour

Yellow

Nominal volume (litres)

11.

Where to buy

[Click here.](#)

Performance

Limitations of use

Thistle GypPrime should be allowed to dry to a tacky surface before plaster is applied

Effect of temperature

Ambient and background temperature must be maintained above 5°C until fully dry. Unused product in tubs must be protected from freezing.

Application

Background preparation: plasterboards

Backgrounds should be reasonably dry, clean and dust-free.

Can be applied by roller or brush onto the background, this can then be plastered when it has soaked into background and has dried.

Background preparation: undercoats

Backgrounds should be reasonably dry, clean and dust-free.

Can be applied by roller or brush onto the background, this can then be plastered when it has soaked into background and has dried.

Mixing up

Thistle GypPrime is supplied ready mixed, at a consistency suitable for hand application. Stir before use, then dilute if necessary to no more than (1:5) 1 part Thistle GypPrime to 5 parts water.

Coverage per bucket (m²)

100m² (undiluted)

Can also be diluted with fresh water at a ratio of 1:5 to give 600m² of coverage

Product Data Sheet

Thistle® GypPrime

Sitework

Storage

Unused product in tubs must be protected from freezing. Avoid stacking more than four high to prevent damage to the packaging.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work Act etc. 1974. However, when designing and installing systems that use British Gypsum products, you must consider the legal requirements set out in:

- 1 Manual Handling Operations Regulations
- 2 Construction (Design and Management) Regulations
- 3 Control of Substances Hazardous to Health Regulations (COSHH).

Safety Data Sheet

Safety Data Sheet (SDS) available [Click here](#).

Shelf life

2 years from production.

Packaging overview

11 litre plastic tub, supplied palletised.

Quantity per pallet	30 tubs
---------------------	---------

Environmental

Recyclability

This product cannot be recycled.

Disposal

Waste should be disposed of in accordance with local authority requirements. Wet waste should be prevented from entering drains.



"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.