


# Technical Specification

This document provides guidance on how to achieve performance and warranty requirements by exclusively using British Gypsum products or system specifications.

GypLynr Independent

## GIWL 92 I 90 PIR (B) (EN)

One layer of Gyproc ThermaLine PIR 38mm to one side of Gypframe 92 I 90 'I' Stud framework forming an independent lining to masonry background. For heights up to 5100mm.



## Background

Background	Masonry
------------	---------

## Head design

Head channel	<b>Gypframe 94 DC 60 Deep Flange Floor &amp; Ceiling Channel</b>
--------------	--

Gypframe channel suitably fixed to soffit at 600mm centres in two lines staggered by 300mm.

Deflection allowance	Vertical deflection only. To be determined by a Structural Engineer.
----------------------	--

Dropped soffit	For principles of deflection head construction refer to detail ST-224-Z2LA-06
----------------	---

## Framework

Stud	<b>Gypframe 92 I 90 'I' Stud</b>
------	----------------------------------

Stud centres - Max (mm)	600
-------------------------	-----

Abutments and openings	<b>Gypframe 92 S 50 'C' Stud</b>
------------------------	----------------------------------

Gypframe 'C' stud suitably fixed to structure at 600mm centres in two lines staggered by 300mm.

Base channel	<b>Gypframe 94 DC 60 Deep Flange Floor &amp; Ceiling Channel</b>
--------------	--

Gypframe channel suitably fixed to floor at 600mm centres in two lines staggered by 300mm.

## Insulation

*No insulation*

## Board and fixings

Board side 1, Layer 1	<b>Gyproc ThermaLine PIR 38mm</b>	Screws side 1, Layer 1	<b>British Gypsum Jack-Point Screws 60mm</b>
-----------------------	-----------------------------------	------------------------	--

Board layer 1, fix securely to Gypframe metal supports around the perimeter of the board and intermediate stud positions at maximum 300mm centres. External corners reduce fixings to 200mm. Drywall screws can be used for fixing boards to metal profiles with a thickness of 0.8mm or less (excluding 'I' studs). Fix working from the centre of each board. Position screws not less than 13mm from cut edges and 10mm from bound edges of boards. Set screw heads flush with plasterboard surface; do not break paper or gypsum core.

Fixing strap	<b>Gypframe GFS1 Fixing Strap</b>
--------------	-----------------------------------

Used to support horizontal board joints and enable board screw fixing at 300mm centres.

Fixing T	<b>Gypframe GFT1 Fixing 'T'</b>
----------	---------------------------------

Used to support horizontal board joints and enable board screw fixing at 300mm centres.

Sealant	<b>Gyproc Sealant</b>
---------	-----------------------

Locate sealant at junctions with adjoining structure and other air paths. Apply as a continuous bead to clean, dry, dust-free surfaces, leaving no gaps. After application of sealant, bulk fill gaps between floor and underside of plasterboard using Gyproc jointing compound.

## Finish coat

The system should be finished using either one of our Thistle or ThistlePro plasters, or Gyproc jointing products. See the product range guides on the British Gypsum website for more information.


# Technical Specification

This document provides guidance on how to achieve performance and warranty requirements by exclusively using British Gypsum products or system specifications.

GypLynr Independent

## GIWL 92 I 90 PIR (B) (EN)

One layer of Gyproc ThermaLine PIR 38mm to one side of Gypframe 92 I 90 'I' Stud framework forming an independent lining to masonry background. For heights up to 5100mm.



## System performance

Please read performance data with any associated standards.

Maximum height (mm)	<b>5100</b>
---------------------	-------------

The maximum heights quoted are based upon a limiting deflection of L/240 at 200 Pa.

Minimum cavity / offset (mm)	<b>30</b>
------------------------------	-----------

The minimum cavity/offset is recommended to avoid bridging between the background and metal studs over the lining system height.

## Further information

**SpecSure®** system performance warranty confirms that British Gypsum proprietary systems will perform as specified for the lifetime of the building. The **SpecSure®** warranty requires that all components are specified in full and constructed in accordance with British Gypsum's installation guidance. For more details see the British Gypsum website. Always check with the design team before making any changes to the chosen specification, ensuring appropriate substantiation is sought to confirm that the solution still meets all required project performances.