

# Declaration of Performance

Thistle® undercoat plaster range



<b>1 Unique identification code of the product type:</b>	Thistle undercoat plaster range
<b>2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</b>	Thistle BondingCoat EN13279 B4/20/2 and C3/20 Thistle HardWall EN13279 B4/20/2 and C3/20
<b>3 Intended use/s:</b>	Gypsum plaster for internal wall linings (base coat)
<b>4 Manufacturer:</b>	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0)115 945 1000
<b>5 Authorised representative:</b>	N/A
<b>6 System/s of AVCP:</b>	System 4
<b>7 Harmonised standard:</b>	EN 13279-1:2008
<b>Notified body/ies:</b>	N/A
<b>8 European Assessment Document:</b>	N/A
<b>European Technical Assessment:</b>	N/A
<b>Technical Assessment Body:</b>	N/A
<b>Notified body/ies:</b>	N/A
<b>9 Declared performance/s:</b>	The characteristics in the table below apply to all products mentioned in 2 above.


Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A1	EN 13279-1:2008
Direct airborne sound insulation <sup>1</sup> (R)	See manufacturer's literature	EN 13279-1:2008
Thermal Resistance (TR)	0.037m <sup>2</sup> K/W (Thistle HardWall) 0.028m <sup>2</sup> K/W (Thistle BondingCoat)	EN 13279-1:2008

<sup>1</sup> These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

## 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....  
**Matt Pullen, Managing Director, British Gypsum**

East Leake 31/05/2019  
.....

**Place and date of issue**