

Declaration of Performance

Thistle® DriCoat



1 Unique identification code of the product type:	Thistle DriCoat
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Thistle DriCoat
3 Intended use/s:	Renovating plastering mortar for internal wall linings (base coat)
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0)115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	System 4 generally
7 Harmonised standard:	EN 998-1:2016
Notified body/ies:	N/A
8 European Assessment Document:	N/A
European Technical Assessment:	N/A
Technical Assessment Body:	N/A
Notified body/ies:	N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A1	EN 998-1:2016
Adhesive strength	0.8N/mm ² , FP A	EN 998-1:2016
Compressive strength	CS II	EN 998-1:2016
Dry Bulk Density (declared)	725kg/m ³	EN 998-1:2016
Water absorption	6.52kg/m ² after 24 hr	EN 998-1:2016
Water vapour Diffusion Coefficient (μ)	12.22	EN 998-1:2016
Thermal conductivity (λ)	0.17W/m.K	EN 998-1:2016

Declaration of Performance

Thistle® DriCoat



10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....
Matt Pullen, Managing Director, British Gypsum

East Leake 08/05/2019

.....
Place and date of issue