

Declaration of Performance

Certificate No. 0011-CPR-22v1
CE

1.

Unique identification of the product type:

Steel Frame Infill Batt

2.

Type, batch or serial number or any element allowing identification of the construction product as required under Article 11(4) of the CPR:

See product label

3.

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings (ThIB)

4.

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Saint-Gobain Isover UK Limited, Whitehouse
Industrial Estate, Runcorn, Cheshire, WA7 3DP, UK**

5.

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6.

System or systems of Assessment and Verification of Constancy of Performance (AVCP) of the construction product as set out in Annex V:

**System 1 (Reaction to fire)
System 3**

7.

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified certification body Element Materials
Technology Rotterdam B.V. No. 2812 performed, carried
out the determination of the product type, the initial
inspection of the manufacturing plant and of factory
production control and the continuous surveillance,
assessment and evaluation of factory production
control and issued the certificate of constancy of
performance (2812-CPR-BA0053) for Reaction to fire.**

8. Declared performance

Harmonised Technical Standard: EN 13162:2012 + A1:2015

Essential characteristics	Performance	Unit	Declared performance		
Product name			Steel Frame Infill Batt		
Reaction to fire		Euroclass	A1		
Release of dangerous substances to the indoor environment	Release of dangerous substances (e)		NPD		
Acoustic absorption index	Sound absorption		NPD		
Impact noise transmission index	Dynamic stiffness		NPD		
	Thickness		NPD		
	Compressibility		NPD		
	Air flow resistivity		NPD		
Direct airborne sound insulation index	Air flow resistivity		NPD		
Continuous glowing combustion	Continuous glowing combustion (e)		NPD		
Thermal resistance	Thermal resistance	m ² .K/W	1.35	2.05	2.75
	Thermal conductivity	W/(m.K)	0.036	0.036	0.036
	Thickness	mm	50	75	100
	Thickness class		T4	T4	T4
Water permeability	Short term water absorption		NPD		
	Long term water absorption		NPD		
Water vapour permeability	Water vapour transmission		NPD		
Compressive strength	Compressive stress or compressive strength		NPD		
	Point load		NPD		
Durability of Reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (a)	Euroclass	A1		
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (b)	m ² .K/W	1.35	2.05	2.75
	Thermal conductivity (b)	W/(m.K)	0.036	0.036	0.036
	Durability characteristics (c)		NPD		
Tensile/flexural strength	Tensile strength perpendicular to faces (d)		NPD		
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep		NPD		

NPD No Performance Determined

(a) No change in Reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.

(b) Thermal conductivity of mineral wool products does not change with time.

(c) For dimensional stability thickness only.

(d) This characteristic also covers handling and installation.

(e) European test methods are under development.

Declaration of Performance


Document No. 0011-CPR-22v1
19 - 05 - 2022

9.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'Dean O'Sullivan', written in a cursive style.

Dean O'Sullivan, Managing Director

Runcorn.

19th May 2022



Isover

Whitehouse Industrial Estate,
Runcorn WA7 3DP

**Customer Service -
Order Placement and Enquiries**

Tel: 01473 820820
Email: iukcustomerservice@saint-gobain.com

Technical Support Centre

Tel: 01473 820850
Email: technicalsupport@saint-gobain.com

insulation-uk.com

Published date: May 2022
Certificate No.: 0011-CPR-22v1

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at insulation-uk.com

Isover: Whitehouse Industrial Estate, Runcorn, Cheshire, WA7 3DP. Tel +44 (0) 1473 822093.
Saint-Gobain Isover UK Limited, Registered in England. Company Number 10442670.
Registered Office: Saint-Gobain House, East Leake, Loughborough, Leicestershire LE12 6JU.