# **Product data sheet**

## Gypframe® GL12 Bracket



Steel GypLyner Brackets.

## Where to use

For connecting the Gypframe GL1 Lining Channel to the soffit with a maximum 175mm stand-off.

## **Certifications**

Environmental Product Declaration (EPD) available Click here.



## **Product information**

## Composition

Steel.

Where to buy Click here.

#### Colour

Steel.

| DIMENSIONS AND WEIGHTS   |      |                                      |
|--------------------------|------|--------------------------------------|
| Lenths available (mm)    | 175  |                                      |
| Bespoke length available | No   | 395mm  175mm  45mm  175mm            |
| Width (mm)               | 45   |                                      |
| Gauge (mm)               | 0.50 | As supplied — 66 no. 4.25 dia. holes |
| Weight (kg/lm)           | -    |                                      |

## **Performance**

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

#### **Standards**

EN 13964:2014.

Declarations of Performance (DoP) available Click here.

| Reaction to fire       | A1  |
|------------------------|-----|
| Yield strength (N/mm²) | 140 |

## Installation guidance

Please see our White Book online for more information about installing and handling British Gypsum systems and Gypframe profiles. See the Gypframe Safety Data Sheet for guidance on health and safety, handling and storage.

## Fixing compatibility

Check the system specification for the required British Gypsum screw type.

## **Product data sheet**

# Gypframe® GL12 Bracket



## **Sitework**

## **Safety Data Sheet**

Gypframe metal components Safety Data Sheet (SDS) available. Click here.

## **Packaging overview**

Supplied in a cardboard box.

| Quantity per pack | 100 |
|-------------------|-----|
|                   |     |

## **Environmental**

## Recyclability

Gypframe components are 100% recyclable.

## **Disposal**

Waste from Gypframe metal framing components is fully recyclable. The European Waste Catalogue code is 12 01 01.



British Gypsum Head Office, East Leake, Loughborough, Leicestershire, LE12 6HX T: 0115 945 1000



"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited.
"Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

 $\hbox{``British Gypsum'' is a registered trademark of Saint-Gobain Construction Products UK Limited.}$