

Product data sheet

Gypframe® LF7 Connector

Gypframe LF7 Connector for use between stud and head channel.

Where to use

Gypframe LF7 Connector can be used in specific British Gypsum GypWall Single Frame partition system to reduce the coefficient of static friction between adjacent Gypframe components.



Product information

Composition

Polypropylene.

Colour


Off-white.

Where to buy

[Click here.](#)

DIMENSIONS AND WEIGHTS

Lengths available (mm)	147
Bespoke length available	No
Width (mm)	70
Gauge (mm)	-
Weight (kg/lm)	-



Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

No harmonised standard.

Reaction to fire	E
------------------	---

Installation guidance

Please see our White Book online for more information about installing and handling British Gypsum systems and Gypframe profiles. See the Gypframe LF7 Connector Safety Data Sheet for guidance on health and safety, handling and storage.

Fixing compatibility

The Gypframe LF7 Connector designed to friction fit into the Gypframe 70mm 'C' and 'I' Stud profiles.

Product data sheet

Gypframe® LF7 Connector

Sitework

Storage

The products should be stored inside on a flat and stable surface, away from any sources of moisture, heat or direct sunlight. If storing on a concrete floor, use dry timber platforms.

The products should not be stored near any edges, openings, walkways or traffic areas, where they could fall or cause obstruction.

Handling

British Gypsum fully accepts its responsibilities as a supplier of building materials and systems as required by Section 6 of the Health and Safety at Work etc. Act 1974.

To reduce manual handling risk, employers and workers should follow HSE's Manual Handling Operations Regulations 1992 (MHOR) and the HSE's guidance on manual handling at work (INDG143). Employers should carry out a risk assessment and implement control measures to avoid or minimise the need for manual handling. Workers should follow safe lifting and moving techniques and report any hazards.

When handling British Gypsum metal accessories please ensure you are wearing puncture-resistant protective gloves, sleeves and appropriate safety footwear.

Personal protective equipment for eye and face protection should also be worn that comply with European Standard EN166.

Safety Data Sheet

Gypframe LF7 Connector Safety Data Sheet (SDS) available. [Click here.](#)

Packaging overview

Supplied in a cardboard box.

Quantity per pack	120
-------------------	-----

Environmental

Recyclability

Gypframe components are 100% recyclable.

Disposal

Gypframe LF7 Connector is recyclable. The European Waste Catalogue code is 17 02 03.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Okarno" is a registered trademark of Okarno Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Okarno Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.