

Product Data Sheet

Gyptone Quattro 46 Access Hatch

The Gyptone Quattro 46 Access Hatch creates virtually invisible access to services, seamlessly blending in with surrounding tiles. It maintains the ceiling's acoustic performance with an acoustic backing and 12mm square perforations that absorb noise.

All Gyptone products contain ACTIVair® which makes indoor air healthier by eliminating up to 70% of formaldehyde present in indoor air.

The access hatch comes in a two-part system that's simple to install, including a 600mm frame and a 510mm tile.

Where to use

Use it with the GypCeiling MF suspended ceiling system for quick and easy access to ceiling void services without compromising on aesthetics.



Product information

Composition

Gypsum core with sound absorbent tissue bonded to the rear and an unpainted face.

Backing tissue colour

Light grey.

DIMENSIONS AND WEIGHTS

Lengths available (mm)	600
Width (mm)	600
Nominal thickness (mm)	12.5
Hatch opening length (mm)	510
Hatch opening width (mm)	510
Perforation shape	Square
Perforation width (mm)	12
Perforation length (mm)	12
Perforation spacing (mm)	25
Edge type availability	B
Weight per carton (kg)	4.4

Product Data Sheet

Gyptone Quattro 46 Access Hatch

Performance

Here we only provide performance information related to the product. Please see the White Book online for system-dependent performance.

Standards

EN 14190:2014.

Declarations of Performance (DoP) available [Click here](#).

Reaction to fire	A2-s1, d0
Specialist performance	Contains ACTIVair® technology
Moisture resistance (maximum % RH)	70
Maximum continuous temperature (°C)	45

Limitations of use

Gyptone products should be used in areas with a relative humidity that does not constantly exceed 70% or temperature of 45°C.

Fixtures

Don't use Gyptone Hatch products to support fixtures.

Installation guidance

Please see our White Book online for more information about installing and handling British Gypsum systems.

Painting

The Gyptone access hatch has an untreated surface. It should be primed using Gyproc Drywall Primer before coating with matt emulsion paint using a short-haired roller. Don't spray paint as this affects the ability to absorb sound.

Product Data Sheet

Gyptone Quattro 46 Access Hatch

Sitework

Storage

Gyptone products should be stored flat on a level surface and protected from dampness. Take care to avoid damage to the acoustic tissue bonded to the back face.

Safety Data Sheet

Safety Data Sheet (SDS) available. [Click here.](#)

Packaging overview

Tiles per carton	1
Cartons per pallet	24
Tiles per pallet	24

Environmental

Recyclability

Gyptone products are 100% recyclable.

Disposal

British Gypsum operates a Plasterboard Recycling Service; please call 0800 6335040 for further information. Alternatively, segregate the product from non-gypsum waste for recycling where possible, and dispose of it according to local authority requirements.



"Gyproc", "Thistle", "ThistlePro", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover (French legal entity) and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.