

Repair range selector guide



Product	Gyproc EasiFill 60	Gyproc EasiFill 20	Thistle One Coat Plaster	Thistle Bonding 60	Thistle Undercoat Plaster	Thistle Finishing Plaster
Product description	Easy to finish, quick to decorate	Easy, fast finish for small areas	One bag for undercoat and finishing	Deep patches fast	Larger areas and deep patches	Traditional method for the finest finish
What's it best for?	Up to 6mm deep holes, patches and cracks	Up to 6mm deep holes, patches and cracks	Repairs and patches holes deeper than 5mm	Small patches, repairs or chases deeper than 5mm	Patches, repairs or chases deeper than 5mm	A fine, smooth, durable finish for patches, cracks, repairs and chases up to 6mm deep
What sort of jobs can it do?	Filling around socket boxes, repairing movement cracks, filling knocks or damage. Patching larger areas of plasterboard	Filling around socket boxes, repairing movement cracks, filling knocks or damage. Patching small areas of plasterboard	Larger repairs on water or impact damaged plaster, filling pipe or cable chases, making block or brick walls ready for decoration	Smaller repairs on water or impact damaged plaster, filling pipe or cable chases, deep holes (built up in coats)	Larger repairs on water or impact damaged plaster, filling pipe or cable chases, deep holes (built up in coats)	To finish a repair job when used on Thistle Bonding 60 or Thistle Undercoat Plaster
How do I finish it?	Sand to a fine, white finish before painting	Sand to a fine, white finish before painting	Trowel to a smooth finish and allow to fully dry before decoration	Apply a finish coat of Thistle Finishing Plaster, following application instructions as required	Apply a finish coat of Thistle Finishing Plaster, following application instructions as required	Trowel to a smooth finish, allow to fully dry before priming and painting
How long does it stay workable?	60 mins	20 mins	45 mins	45 mins	80 mins	40 mins
How quickly can I finish it?*	130 mins	60 mins	90 mins	75 min	200 mins	-
How soon can I decorate it?*	24 hours	24 hours	48 hours	-	-	48 hours
Pack size	10kg bag	5kg bag	12.5kg bag	10kg tub, 12.5kg or 25kg bags	12.5kg bag	12.5kg bag
Where to use - background surface						
Lightweight blocks, common bricks	-	-	Y	-	-	-
Undercoat plaster	-	-	-	-	-	Y
Dense blocks	-	-	Y	Y	Y	-
Plasterboards and Glasroc boards	Y	Y	Y	Y	Y	Y
Concrete	-	-	Y	Y	Y	Y
Painted surfaces	-	-	Y	Y	Y	Y
Metal lathing	-	-	Y	Y	Y	-

Thistle Bond-it may be required for repairs on smooth/low suction such as dense blocks, MR boards, concretes and painted surfaces. Thistle GypPrime may be required for very high suction backgrounds such as undercoat plaster.

* Dependent on environmental conditions.