

Gyproc Habito Corners

Product Data Sheet

Product description

Overview

Gyproc Habito Corners is suitable for application to any external or internal plasterboard corner and can be used for uprights, reveals, bulkheads, columns, splays and raked ceilings. Due to its durability, Gyproc Habito Corners is great for high traffic areas.

Applications

Gyproc Habito Corners provides a perfect corner to any angle every time. Applied with Gyproc Joint Filler or Gyproc QuickSand Joint Cement, it has a uniform, strong, structural bond because of its paper backing preventing cracking and call backs. High quality formulated face paper is perfect for applying paint or texture. Great for all off-angles, stand ups and areas of irregular framing. Gyproc Habito Corners is suitable for plastering, and is ideal for creating straight lines in raked ceilings. Gyproc Habito Corners comes in a 30m roll.

Range

Length m	Width mm	Weight per roll kg	Colour	Finish texture	Rolls per carton	Pallet quantity carton
30	83	1.9	White	Paper	10	40

Application and installation

Background preparation

Plasterboard surfaces should be dry, clean and protected from the weather. Boards should be securely fixed with no steps between adjacent boards. The correct fixings must be used and properly located with their heads just below the liner surface. Any protruding screw heads should be driven home with a hand screwdriver, prior to spotting and jointing. Gaps between boards greater than 3mm should be pre-filled using Gyproc Joint Filler, or Gyproc EasiFill, prior to application of Gyproc Habito Corners.

Storage

Boxes should be stored in a dry location, as significant water ingress could damage the product. Boxes should not have other materials stacked on top of them.

Preparation

Gyproc Habito Corners can be cut to length using scissors or metal snips.

Installation

Open the Gyproc Habito Corners box and feed product through slot on side of box.

Insert the hook of a tape measure into narrow slot to measure length of Gyproc Habito Corners needed.

Cut to length with scissors or snips. With a 4" – 6" taping knife, apply Gyproc Joint Filler or Gyproc QuickSand Joint Cement to the corner and press the Gyproc Habito Corners into position. Remove the excess Gyproc Joint Filler or Gyproc QuickSand Joint Cement with the same knife and allow the product to dry.

Finishing

Use a 6" – 8" finishing knife to skim over edges of corner using any of the Gyproc QuickSand Joint Cement products. Allow to dry before sanding to a fine finish.

Maintenance

If the product is correctly applied and not exposed to moisture or mechanical damage, it should not require any form of maintenance. If the Gyproc Habito Corners suffers serious damage after installation, small sections may be cut out and replaced using the normal installation method.

"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of Saint-Gobain Construction Products UK Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Construction Products UK Limited.

Saint-Gobain Construction Products UK Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. Saint-Gobain Construction Products UK Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of Saint-Gobain Construction Products UK Limited.

T: 0115 945 6123
F: 0115 945 1616
E: bgtechnical.enquiries@bpb.com

Training enquiries: 0844 561 8810

British Gypsum April 2019 BG-PDS-311-04

