

# Gyproc SoundBloc RAPID MR

## Product Data Sheet

### Introduction

Used in the British Gypsum GypWall RAPID system, a quick to erect, high performance internal wall system for housing applications.

### Product description

Gypsum plasterboard with moisture resistant additives and a higher density core, in a special dimensional configuration. Gyproc SoundBloc RAPID MR consists of an aerated gypsum core with water repellent and other additives encased in, and firmly bonded to, strong paper liners. Gyproc SoundBloc RAPID MR is a plasterboard that is suitable for drylining internal surfaces.

This plasterboard is one of the products within our plasterboard range that is certified to BES 6001 achieving a rating of 'Very Good'.



### Board performance

#### Fire protection

Plasterboard linings provide good fire protection owing to the unique behaviour of the non-combustible gypsum core when subjected to high temperatures. For the purposes of the national Building Regulations, plasterboard is designated a 'material of limited combustibility' (Approved Document B). The surfaces of Gyproc SoundBloc RAPID MR are designated Class 0 (for the purposes of national Building Regulations). Please refer to the table below.

#### Fire resistance / sound insulation

Please refer to the appropriate White Book product or system section for information on the fire resistance and sound insulation of building elements lined with Gyproc SoundBloc, available to download at [www.british-gypsum.com](http://www.british-gypsum.com). The substitution of Gyproc SoundBloc with the same thickness of Gyproc SoundBloc RAPID MR will not change the fire or sound insulation performance.

#### Reaction to fire test performance

| Standard   | Performance   |
|--|---|
| BS 476: Part 6: 1989 Method of test for fire propagation for products. | Index of performance (I) not exceeding 12 and a sub-index (i1) not exceeding 6. |
| BS 476: Part 7: 1997 Surface spread of flame tests for materials.      | Class 1 (both sides).   |
| EN 520: 2004.  | Classified without further testing as A2-s1, d0.                                |

#### Thermal conductivity

Gyproc SoundBloc RAPID MR - 0.25W/mK

#### Effect of temperature

Gyproc SoundBloc RAPID MR is unsuitable for use in areas subject to continuously damp or humid conditions, i.e. above 70% RH, and must not be used to isolate dampness. Plasterboards are not suitable for use in service temperatures above 49°C, but can be subjected to freezing conditions without risk of damage.

#### Effect of condensation

The thermal insulation and ventilation requirements of national Building Regulations aim to reduce the risk of condensation and mould growth in new buildings. However, designers should take care to eliminate all possibility of problems caused by condensation, particularly in refurbishment projects.

#### Moisture resistance

The total water absorption of Gyproc SoundBloc RAPID MR is ≤ 5% when tested in accordance with EN 520, clause 5.9.2.

#### Board colour

- Blue face paper
- Green reverse side paper

#### Board printing

Face - screw centre markings 'x'.  
Edge - product code, EAN number, board thickness x width x length, edge type.  
Reverse - standard and certification.

#### Board range

| Width mm                 | Length mm | Edge type   |
|--------------------------|-----------|---|
| <b>15mm Board</b><br>900 | 2400      | Kg/m <sup>2</sup> = 12.6 R (m <sup>2</sup> K/W) = 0.06<br>T/E |

T/E = Tapered Edge

#### Board types

T/E - with Gyproc jointing materials for taped and filled joints or as a base for tiling.

# Application and installation

## General

It is important to observe appropriate health and safety legislation when working on site i.e. personal protective clothing and equipment, etc. The following notes are intended as general guidance only. In practice, consideration must be given to design criteria requiring specific project solutions

## Handling

Manual off-loading of this product should be carried out with care to avoid unnecessary strain. For further information please refer to the Manual Handling section of the **Site Book** or Manual Handling Guide, available to download from [www.british-gypsum.com](http://www.british-gypsum.com).

## Cutting

This product may be cut using a plasterboard saw or by scoring with a sharp knife and snapping the board over a straight edge. Holes for switch or socket boxes should be cut out before the boards are fixed using a utility saw or sharp knife. When cutting boards, power and hand tools should be used with care and in accordance with the manufacturers' recommendations. Power tools should only be used by people who have been instructed and trained to use them safely. Appropriate personal protective equipment should be used.

## Fixing

Fix boards with decorative side out to receive joint treatment or a skim plaster finish. Lightly butt boards together. Never force boards into position. Install fixings not closer than 13mm from cut edges and 10mm from bound edges. Position cut edges to internal angles whenever possible, removing paper burrs with fine sandpaper. Stagger horizontal and vertical board joints between layers by a minimum of 600mm. Locate boards to the centre line of framing where this supports board edges or ends.

## Plastering

Skim plastering should not normally be specified to Gyproc Moisture Resistant and MR grade boards. These types of board are intended for use in environments of higher than normal humidity for which no gypsum plaster is designed to be suitable. Where moisture resistant board options are used in shell and core construction to provide temporary resistance to high moisture conditions, they can be skimmed at a later date after the building envelope has been made weather-tight. Plaster should be applied only to the face of moisture resistant boards and pre-treatment with ThistleBond-it is required.

## Jointing

Gyproc jointing materials produce durable joint reinforcement and a smooth, continuous, crack-resistant surface ready for priming and final decoration. A number of jointing specifications are available to suit the board type, method of application, and site preference.

## Decoration

After the joint treatment has dried, decoration, including any decorator's preparatory work, should follow with the minimum delay.

---

## Product standards

*EN520: 2004 + A1: 2009 Gypsum Plasterboards, definitions, requirements and test methods.*

**Type D:** Gypsum plasterboard with control density.

These boards have a controlled density, with a face to which decoration may be applied. This enables improved performance in certain applications to be obtained.

**Type H1:** Plasterboard with reduced water absorption rate.

Boards which have additives to reduce the water absorption rate. They may be suitable for special applications in which reduced water absorption properties are required to improve the performance of the board. For the purposes of identification, these boards are designated Type H1, H2 and H3, with different water absorption performance.

# Maintenance

## Repair

**Minor damage** - Lightly sand the surface to remove burrs and fill flush with Gyproc Easi-Fill or Gyproc Easi-Fill 45, or two applications of Gyproc Joint Cement. When dry, apply Gyproc Drywall Primer or Gyproc Drywall Sealer to leave the surface ready for decoration.

**Deep indents resulting from impact** - Check the plasterboard core to ensure that it is not shattered. If intact, apply a coat of Gyproc Joint Filler, or Gyproc Easi-Fill or Gyproc Easi-Fill 45, followed by the procedure for repairing minor damage as outlined above, once set / dry.

**Damaged core and / or broken edges (non-performance situations only)** - Remove the damaged area of core. Score the liner approximately 10mm away from the sound plaster around the damaged area, and peel the paper liner away. Apply Thistle GypPrime or PVA to seal the core and surrounding liner. Bulk fill the hole with a stiff mix of Gyproc Easi-Fill or Gyproc Easi-Fill 45, or Gyproc Joint Filler, and strike off flush. Apply Gyproc Easi-Fill or Gyproc Easi-Fill 45, or two applications of Gyproc Joint Cement, once the filler is set / dry. When dry, apply Gyproc Drywall Primer or Gyproc Drywall Sealer (only suitable in non-performance situations)

**Extensive damage** - When the damage is more extensive, it may be necessary to replace that area of plasterboard. It is important that the replacement board is of the same type as specified and installed. Cut out the affected area back to the nearest framing member. Replace the plasterboard, accurately cutting and screw fixing the same type and thickness of plasterboard. Fill edge joints, then tape and finish in the recommended way. Treat the finished surface with Gyproc Drywall Primer or two coats of Gyproc Sealer, if previously specified for vapour control purposes. Redecorate as required.

**NB** It is essential that repairs are made 'like for like'. If the finish is skim plaster, jointing materials must not be used in the repair.

Date of previous version: November 2008

"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of BPB United Kingdom Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of BPB United Kingdom Limited.

BPB United Kingdom Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. BPB United Kingdom Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: [www.british-gypsum.com](http://www.british-gypsum.com). For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of BPB United Kingdom Limited.

**Telephone: 0844 800 1991**

**Fax: 0844 561 8816**

**Email: [bgtechnical.enquiries@bpb.com](mailto:bgtechnical.enquiries@bpb.com)**

**Training enquiries: 0844 561 8810**



EMS 543324 FM 550533

© British Gypsum May 2014 PDS-017-02

[www.british-gypsum.com](http://www.british-gypsum.com)

