

Declaration of Performance

Glasroc F FireCase

GLAS102

1. Unique identification code of the product-type:

Glasroc F FireCase

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Glasroc F FireCase: 15mm, 20mm, 25mm, 30mm
EN 15283 - GM-F, GM-H1**

3. Intended use/es:

Plasterboard lining

4. Manufacturer:

**British Gypsum
Registered in England 734396
East Leake, Loughborough, Leicestershire LE12 6HX
Tel: +44 (0) 115 945 1000**

5. Authorised representative:

N/A

6. System/s of AVCP:

**System 4 generally
System 3 Reaction to Fire**

7. Harmonised standard:

EN 15283-1: 2008 + A1: 2009

Notified body/ies:

MPA Hannover (NB 0764)

Performed:

Reaction to Fire

Under:

System 3

8. European Assessment Document:

N/A

European Technical Assessment:

N/A

Technical Assessment Body:

N/A

Notified body/ies:

N/A

9. Declared performance/s:

The characteristics in the table below apply to all products mentioned in 2 above.

| Essential Characteristics | Performance | Harmonised technical specification |
|--|-------------------------------|------------------------------------|
| Longitudinal flexural strength (F) | 645N (15mm) | EN 15283-1: 2008 +A1: 2009 |
| | 860N (20mm) | EN 15283-1: 2008 +A1: 2009 |
| | 1075N (25mm) | EN 15283-1: 2008 +A1: 2009 |
| | 1290N (30mm) | EN 15283-1: 2008 +A1: 2009 |
| Transverse flexural strength (F) | 252N (15mm) | EN 15283-1: 2008 +A1: 2009 |
| | 336N (20mm) | EN 15283-1: 2008 +A1: 2009 |
| | 420N (25mm) | EN 15283-1: 2008 +A1: 2009 |
| | 504N (30mm) | EN 15283-1: 2008 +A1: 2009 |
| Shear strength ($\uparrow\downarrow$) | NPD | EN 15283-1: 2008 +A1: 2009 |
| Reaction to Fire (R2F) | A1 | EN 15283-1: 2008 +A1: 2009 |
| Water vapour permeability (μ) | 10 | EN 15283-1: 2008 +A1: 2009 |
| Impact resistance ¹ (\rightarrow I) | See manufacturer's literature | EN 15283-1: 2008 +A1: 2009 |
| Direct airborne sound insulation ¹ (R) | See manufacturer's literature | EN 15283-1: 2008 +A1: 2009 |
| Acoustic absorption ¹ (α) | See manufacturer's literature | EN 15283-1: 2008 +A1: 2009 |
| Thermal resistance (as conductivity) (λ) | 0.3W/mK | EN 15283-1: 2008 +A1: 2009 |


¹These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

10. Appropriate Technical Documentation and / or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Matt Pullen, Managing Director British Gypsum



.....
(Signature)

East Leake 26/03/2019

.....
(Place and date of issue)

"British Gypsum" is a registered trade name of Saint-Gobain Construction Products UK Limited. Saint-Gobain Construction Products UK Limited (Company no. 734396) registered office Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK